



S12U16/S34U18 series smart meter

IDIS  DLMS® KEMA Labs



S12U16/S34U18 meter series is a solution for industrial, commercial and residential customers. It has strong functionality, and provides interoperability and external communication technology. The solution can act as a gateway for collecting data from gas, heat and water meters. It has various user interface, anti-tampering function, high secure encryption technology, etc. Flexible and modular design can meet today's rapidly changing markets.

Key Features

Electronics

- Active, reactive and apparent energy measurement
- Accuracy up to Cl.1/Cl.B (MID) [active energy] and Cl.2 [reactive energy]
- Wide range measurement from starting current to maximum current
- Up to 8 tariffs
- Button for display control, Button with sealing for manual billing.
- Optical & RS485 & Mbus & P1 interface
- Utility meter read (read consumption from gas, water and heat meters)

Functions

- Loadprofile/billing/event record
- DLMS, IDIS
- FW upgrade for meter and module
- High secure communication suite 0/1
- Interchangeable modules
- Anti-Tampering for strong magnetic/ abnormal wiring/cover removed, etc.

Housing


- Installation standard according to DIN 43857
- Polycarbonate with glass fibre, flame retardant and heat-proof
- IP54

▲ Technical Specifications


Model		S12U16	S34U18	S34U18 CT	S34U18 CTVT	
Accuracy	Active	Cl.1/Cl.B	Cl.1/Cl.B	Cl.0.5	Cl.0.5	
	Reactive	Cl.2	Cl.2	Cl.1	Cl.1	
Voltage	Rated	220V	3×220V/380V	3×220V/380V	3×57.7V	
		230V	3×230V/400V	3×230V/400V	3×120V	
	Range	240V	3×240V/415V	3×240V/415V	3×220V	
			0.6Un-1.15Un	0.6Un-1.15Un	3×230V	
Frequency		50Hz/60Hz	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz	
Current	Range	5 (60) A	5 (60) A	1.5 (6) A	1.5 (6) A	
		5 (80) A	5 (80) A	5 (10) A	5 (10) A	
Display		8 digits	8 digits	8 digits	8 digits	
Remote communication type		4G/3G/2G/PLC/RF	4G/3G/2G/PLC/RF	4G/3G/2G	4G/3G/2G	

▲ Dimensions

S12U16
Single phase smart meter



S34U18(DC/CT/CTVT)
Three phase smart meter



NINGBO SANXING SMART ELECTRIC CO., LTD.

Tel: +86-574-88072218

Fax: +86-574-88220583

E-mail: info@overseas.sanxing.com

Add: No.16,Fenglin Road ,China ,315031